



Zen-O™
Portable Oxygen Concentrator

Give your patients more freedom
with mobile oxygen on demand



Gas Control Equipment

SIMPLE. PORTABLE. DEPENDABLE.

MAXIMISE YOUR PATIENTS' INDEPENDENCE AND PEACE OF MIND

You can help many of your oxygen patients to live their lives more independently with the Zen-O™ portable oxygen concentrator from GCE Healthcare.

The mobile, lightweight Zen-O™ will enable most of your patients to live an active lifestyle. Zen-O™ will also help ease any anxieties some might have about being left without supplementary oxygen.



DESIGNED FOR PATIENTS

We've worked hard to make sure Zen-O™ delivers oxygen to your patients when and where they need it most.

Zen-O™ uses patented technology that quietly adjusts the flow rate of oxygen in response to a patient's breath rate. For example, if your patient climbs some stairs and the device detects the need for more oxygen, it automatically increases the amount delivered to ensure they remain saturated.



PULSE AND CONTINUOUS FLOW

Zen-O™ gives patients the choice of either pulse or continuous flow rates at up to 2 litres per minute of oxygen produced.

Your business will also benefit, as Zen-O™ enables you to meet the oxygen needs of most of your patients.

SIMPLE. PORTABLE. DEPENDABLE.

LOW COST TO OXYGEN PROVIDERS

While Zen-O™ delivers freedom, choice and peace of mind to patients, home oxygen providers will find it easy to maintain and so the cost of ownership is low.



NO WAITING OR RETURNS

When the sieve bed needs to be replaced, there's no need to incur costs by sending it back to GCE Healthcare or an authorised distributor for maintenance. Best of all, your patients don't have to wait for its return.

Zen-O's design means your trained staff can use simple tools to carry out basic maintenance, such as replacing the sieve bed. It just takes a few minutes.

And, after the sieve bed has been successfully replaced, Zen-O™ can be updated using a combination of buttons on the display.

Our global presence and robust supply chain means replacement parts and accessories are readily available.

FLEXIBILITY TO GO WITH THE FLOW

Weighing just 4.66kg (10lbs), the Zen-O™ offers lightweight portability, which means patients can carry on with their lives unrestricted.

With its intuitive buttons and clear LCD display, many of your patients will find the ultra-reliable Zen-O® simple to operate in all kinds of environments.



ONE SOLUTION

Zen-O™ comes with everything most patients need to remain mobile, including an unobtrusive carry bag, functional pull cart, handy DC and AC power cords, a user manual and quick reference guide that are easy to understand.

Your device will include a re-chargeable lithium-ion battery for use away from home. Zen-O™ can hold up to two batteries that can last up to eight hours in pulse mode.



SIMPLE. PORTABLE. DEPENDABLE.

BUILT TO LAST

Manufactured with pride in the UK and to the highest standards, Zen-O™ will perform so quietly, reliably and unobtrusively, your patients will hardly know it's there.

Zen-O™ portable oxygen concentrator is supplied with a three year device warranty or 15,000 hours of total use for extra assurance.

Zen-O™ is built using carefully selected components and accessories. It's designed to withstand everyday use and an internationally recognised testing facility has independently tested and assessed it to extensive and exacting standards.

MANUFACTURED TO HIGH STANDARDS

Zen-O™ meets the requirements of the;

- European Medical Device Directive
- United States Food and Drug Administration
- Radio Technical Commission for Aeronautics



SPECIFICATIONS

Size (WxDxH):	212 mm × 168 mm × 313 mm (8.3" × 6.6" × 12.3")
Weight:	4.66 kg with one 12 cell battery
Power requirements:	AC adaptor: 100-240V AC(+/- 10%) 50-60 Hz in, 24V DC, 6.25A out DC adaptor: 11.5 - 16V DC in, 19V, 7.9A out
Purity:	87% - 96% at all settings
Maximum oxygen discharge pressure:	20.5 psi
Inspiratory trigger sensitivity:	-0.12cm/H ₂ O
Humidity range:	5% to 93% ± 2% non-condensing
Operating altitude:	0 to 9,000 ft relative to sea level (0 km to 2.7 km)
Temperature:	
Operation:	5°C (41°F) and 40°C (104°F)
Storage:	-20°C (-4°F) and 60°C (140°F)
Setting:	Adjustable in 0.5 increments from 1.0 to 6.0 in pulse mode and from 0.5 to 2.0 in continuous mode
Noise level:	38 dB(A) tested according to Prüfmethode 14-1 03/2007 MDS-Hi* 42 dB(A) tested according to ISO 3744*
Alarm types:	Low oxygen purity No breath detected Low battery Service required
Battery duration:	Up to 4 hours with a single battery or 8 hours with 2 batteries at 18 BPM

*At pulse setting 2.

EUROPE

CZECH REPUBLIC

GCE Trade s.r.o.
Zizkova 381
CZ-583 01 Chotebor
Phone: +420 569 661 122
Fax: +420 569 661 107
sales.cz@gcegroup.com

FRANCE

GCE S.A.S.
70, rue du PUIITS CHARLES
BP N° 40110
FR-58403 La Charité-sur-Loire
Phone: +33/3 86 69 46 00
Fax: +33/3 86 70 09 15
sales.fr@gcegroup.com

GERMANY

GCE GmbH
Weyherser Weg 8
36043 Fulda
Phone: +49 (0)661-8393-0
Fax: +49 661 8393 25
sales.de@gcegroup.com

HUNGARY

GCE Hungária Kft.
II. Rákóczi Ferenc út 68.
H-2314 Halásztelek,
Phone: +36 (24) 521 200
Fax: +36 (24) 521 201
sales.hu@gcegroup.com

ITALY

GCE Mujelli spa
Via F. Cervi, 11
37036 San Martino B.A. (VR)
Phone: +39 045 878 0 525
Fax: +39 045 878 0 750
sales.it@gcegroup.com

POLAND

GCE Sp z o.o.
ul. Dłapińska 12
03-581 Warszawa
Phone: +48 22 511 23 57
Fax: +48 22 677 70 90
sales.pl@gcegroup.com

PORTUGAL

GCE Portugal
Rua do FeiraPark, 50, Piso
2, sala 8
PT-4520-632 São João de Vêr
Phone: +351 256 373 682
Fax: +351 256 378 260
sales.pt@gcegroup.com

RUSSIA

GCE Krass OOO
Russian Federation
129343, Moscow,
Urzhymyskaya Street, no 4
Phone: +7 495 745 26 99
Fax: +7 812 323 86 49
sales.ru@gcegroup.com

RUSSIA

GCE Krass OOO
Russian Federation
194100, Sankt Petersburg
Kantemirovskaya, 12A
Phone: +7 812 323 86 21
Fax: +7 812 323 86 49
sales.ru@gcegroup.com

ROMANIA

GCE Romania S.R.L
22, Al.Puskin Street, Ap.1,
Bucharest 1, 011996
Phone: +40 21 316 76 72
Fax: +40 21 316 76 74
sales.ro@gcegroup.com

SPAIN

GCE Ibérica, S.L.U.
Avda. de la Democracia,
7 - Oficina 311
ES-28031 Madrid
Phone: +34 915 711 470
Fax: +34 915 712 756
sales.es@gcegroup.com

SWEDEN

GCE Norden AB
Box 21044
Källvattengatan 9
200 21 Malmö
Phone: +46-40-388300
Fax: +46-40-388353
sales.se@gcegroup.com

UNITED KINGDOM, IRELAND

GCE Ltd.
Unit 100 Empress Park
Penny Lane, St Helens, WA11 9BD
Phone: +44 (0)1942 29 29 50
Fax: +44 (0)1942 29 29 77
sales.gb@gcegroup.com

ASIA

INDIA

GCE India Pvt. Ltd.
59, 1st Floor,
Millers Road, Benson Town,
Bangalore - 560046, Karnataka
Phone: +91 802 363 1685
Fax: +91 802 353 0110
sales.in@gcegroup.com

INDIA

GCE India Representation Office
Offices No. 44 & 45, 2nd Floor,
Crystal Plaza, Hiranandani
Complex,
Sector - 7, Kharghar,
Navi Mumbai. 410 210,
Maharashtra, India
Mobile: +91-9987026546
sales.in@gcegroup.com

CHINA

GCE Gas Control Equipment Co., Ltd.
No.4 Building, 318 Xiao Wan Road
Fengxian District, Shanghai 201401
P.R. China
Phone: +86-21-37198408
Fax: +86-21-37198617
sales.cn@gcegroup.com

AMERICA

LATIN AMERICA

GCE Latín America
Po.Box: 0843-01211
Panamá
Republica de Panamá
Phone: +507 317 61 68
Fax: + 507 317 65 00
sales.pa@gcegroup.com

MEXICO

GCE Gas Control Equipment SA de CV
Miguel de Cervantes Saavedra 193
Ampliación Granada Miguel Hidalgo
Distrito Federal 11529, México
Phone: +52 55 2626 1439
sales.pa@gcegroup.com



Gas Control Equipment
www.gcegroup.com